

# Mirion At Your Service

High temperature industrial cameras from Mirion have been helping operators and engineers optimize and remotely view kilns, boilers, furnaces and glass tanks since the 1980s. Our systems combine temperature measurement, real-time video, and image processing into an enhanced video experience showing measurement information overlaid onto a live video image.



Cement   Pulp and Paper   Steel and Aluminium Furnaces   Waste-To-Energy Plants   Thermal Power and Auxiliary Boilers   Other High Temp Applications

**MIRION IS A GLOBAL LEADER IN RADIATION SAFETY, SCIENCE AND MEDICINE.**

We offer a broad portfolio of products and services that protects people and the planet from the harmful effects of ionizing radiation and accelerates innovation across a diversity of end markets.



Protect What's Next™



# High Temperature Cameras for Industrial Applications



Copyright © 2025 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.



















MKTG-3274 - 01/2025






[MIRION.COM](http://MIRION.COM)



Visit our website to learn more: [mirion.com](http://mirion.com)

## Cameras

		<b>M555™ High Temperature Spyrometer® Camera</b> 	Patented combination of color video camera and scanning pyrometer*; monitors process conditions while measuring the temperature of any area in the field of view. Video image and temperature information are displayed on a VGA monitor. Additional water cooling available.
		<b>M555™ HR High Temperature Spyrometer® Camera</b> 	Patented combination of High Definition Optics, color video camera and scanning pyrometer*; monitors process conditions while measuring the temperature of any area in the field of view. High Definition Video image and temperature information are displayed on a VGA monitor. Additional water cooling available.
		<b>M535™ Lynx® High Temperature Color Camera Series</b> 	Visible Light Color Camera; enables customization of electronics, lenses, filters and other options. Straight or oblique lens tube options available. Includes temperature sensors.
		<b>M530™ Lynx® High Temperature Color Camera Series</b> 	Visible Light Color Camera; enables customization of electronics, lenses, filters and other options. Straight, oblique, or right angle lens tube options available. Compatible with M721 Iris Controller. Additional water cooling available.
		<b>M540™ Lynx® High Temperature Black and White IR Camera Series</b> 	Near IR Black and White Camera; enables customization of electronics, lenses, filters and other options. Able to penetrate gaseous and fine particulate interferences. Straight, oblique, or right angle lens tube options available. Additional water cooling available.
		<b>M560™ High Temperature Solid State IR Camera</b> 	Combines mid-wave imaging core technology with an optional calibrated optical pyrometer. Optimizes the clarity of monitoring slag build-up, smeltbed profile, or product distribution and burn efficiency.

Processors			Accessories	
				
M721™ Remote Auto Iris Controller (OPTIONAL)	M610 S™ Calico™ 3 Dual Infrared Imaging Processor (OPTIONAL)	M215 S™ Spyrometer® 4 Dual Imaging IR Pyrometer Processor (REQUIRED)	M356™ Retract	M408™ Two Stage Air Filter
Allows adjustments to be made to the M530 camera auto-iris from the control room via coax cable, retaining flame details and burner viewing quality.	Supports one or two Mirion cameras, providing precise temperature measurement of up to 32 'free form' zones across the screen.	Supports one or two Mirion cameras, providing both imagery and precise temperature measurement of up to 32 overlaid temperature measurement zones per camera, fully adjustable for size and measurement mode.	Retracts the camera from the most severe heat where the plant supply of air pressure, water or electricity has been interrupted. Includes ruggedized safety air reservoir and additional options.	Provides clean air in industrial environments where there is a higher contaminate content level and where local control and regulation of the air supply to the camera is required.
		✓	✓	✓
		✓	✓	✓
			✓	✓
✓			✓	✓
	✓		✓	✓
			✓	✓

Applications						
						
Cement, Lime and other Rotary Kilns	Clinker and other Grate Coolers	Chemical Recovery and Fluidized Bed Boilers	Steel and Aluminium Furnaces	Thermal Power and other Auxiliary Boilers	Waste to Energy Plants	Other
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓

\*USA Patent 6,667,761

Processors and accessories sold separately to their respective camera(s). M555 Spyrometer is our only camera for which a processor is required; for other cameras the recommended processor is optional.

Each application category (i.e. 'Cement, Lime and other Rotary Kilns') comprises several individual types of application/operations. Certain products are suitable only for some applications/operations within their respective category.