



RAMSYS™

ABPM 201S™

Seismic Alpha Beta Particulate Monitor

Sampling of air extracted from ventilation ducts or stacks. Can withstand seismic conditions. Dynamic compensation of radon and thoron progenies.

DESCRIPTION

The ABPM 201S monitor forms part of the RAMSYS product line.

It has been developed to sample air extracted from ventilation ducts or stacks. A double silicon detector performs the gamma compensation and a radial fin grid limits the scattering of the alpha particles (static compensation) which facilitates the compensation of the radon and thoron solid progenies by the processing algorithms (dynamic compensation). Operating costs are minimized by the autonomous operation through automatic filter advance management.



FEATURES

- ✓ Static and dynamic compensation of the radon and thoron solid progenies
- ✓ Dynamic gamma background compensation
- ✓ Online spectrometry
- ✓ Up to 6 months filter cassette autonomy
- ✓ 1E qualification and embedded safety related software
- ✓ Available under 10 CFR 50 App. B, ASME NQA-1 and IEC 61226 programs for safety related application

ABPM 201S™ SEISMIC ALPHA BETA PARTICULATE MONITOR

PHYSICAL CHARACTERISTICS

- Radiation detected: alpha, beta and gamma
- Detector: dual large area silicon (PIPS® detector)
- Filter type: FSLW
- Typical energy windows:
 - Alpha: 2 MeV to 10 MeV
 - Beta: 80 keV to 2.5 MeV
 - Gamma: 80 keV to 2.5 MeV
- Typical measurement range:
 - Alpha: 10^{-2} to $3.7 \cdot 10^{+6}$ Bq/m³ ($2.7 \cdot 10^{-13}$ to 10^{-4} µCi/cc)
 - Beta: 1 to $3.7 \cdot 10^{+6}$ Bq/m³ ($2.7 \cdot 10^{-11}$ to 10^{-4} µCi/cc)

ENVIRONMENTAL CHARACTERISTICS

- Normal temperature: +5 °C to +40 °C (+41 °F to +104 °F)
- Temperature limit: -5 °C to +55 °C (+23 °F to +131 °F)
- MTBF: > 20 000 hours, with preventive maintenance
- TID: 100 Gy (10^{+4} rad)

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 35 l/min (1.24 scfm)
- Pressure drop: 100 to 350 mbar (1.45 to 5.07 psi)

MECHANICAL CHARACTERISTICS

- Dimensions: 1305 mm x 830 mm x 680 mm (51.4 in x 32.7 in x 26.8 in)
- Weight: ~ 250 kg (~ 551 lb)
- Color: gray RAL 7030 (decontaminable paint)
- Inlet tube connection: Ø 25.4 mm OD (1 in)
- Outlet tube connection: Ø 12 mm OD (1/2 in)

ELECTRICAL CHARACTERISTICS

- Power supply: refer to possible versions
- Data link outputs: one RS232 and two isolated RS485
- Alarm relays: three SPDT relays
- I/O: two isolated analog outputs and one isolated analog input (0/4-20 mA)

SIGNALING

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: three lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC 60761
- Environmental: IEC/IEEE 60780-323, RG 1.97
- Seismic: IEC 60980, IEEE 344
- EMC: 2014/30/EU and 2014/35/EU, EPRI 102323, MIL STD 461, IEC 61000-6-2 and IEC 61000-6-4

VERSIONS

- 230 Vac or 230 Vac + 400 Vac 3Ø or 120 Vac + 400 Vac 3Ø
- Solenoid check sources
- With or without PIS sampler
- Gas grab sampler ports

ACCESSORIES

- Calibration tools
- Software: MASS2™, RAMVISION™, SIMS2™ applications...
- USB converters



MIRION
TECHNOLOGIES

Copyright © 2024 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.