



RAMSYS™

# ABPM 204M™

## Mobile Alpha Beta Particulate Monitor



Small and lightweight extendable sensor to function locally next to the respiratory tract of workers.

### DESCRIPTION

The ABPM 204M monitor forms part of the RAMSYS product line. Its small and lightweight extendable sensor allows this monitor to operate next to the respiratory tract of workers in their area. A dual silicon detector performs the gamma compensation. A processing algorithm provides a dynamic compensation of radon and thoron solid progenies.

Operating costs are minimized through unattended operation, by the use of a continuous filter and the on-line spectroscopy capability. All these features make the ABPM 204M an efficient diversified and cost effective tool.

### FEATURES

- ✓ Dynamic compensation of the radon and thoron solid progenies
- ✓ Dynamic gamma background compensation
- ✓ Optimized beta measurement for environments with low rate of radon
- ✓ On-line alpha spectrometry
- ✓ Up to 6 months filter cassette autonomy
- ✓ Optimized alpha measurement for low energies ( $^{233}\text{U}$ ,  $^{235}\text{U}$ ,  $^{238}\text{U}$ )

# ABPM 204M™ MOBILE ALPHA BETA PARTICULATE MONITOR

## PHYSICAL CHARACTERISTICS

- Radiation detected: alpha, beta and gamma
- Detector: dual large area silicon (PIPS®)
- Filter type: FSLW
- Typical energy windows:
  - Alpha: 2 MeV to 10 MeV
  - Beta: 80 keV to 2.5 MeV
  - Gamma: 80 keV to 2.5 MeV
- Typical measurement range:
  - Alpha:  $10^{-2}$  to  $3.7 \cdot 10^{+6}$  Bq/m<sup>3</sup> ( $2.7 \cdot 10^{-13}$  to  $10^{-4}$  µCi/cc)
  - Beta: 1 to  $3.7 \cdot 10^{+6}$  Bq/m<sup>3</sup> ( $2.7 \cdot 10^{-11}$  to  $10^{-4}$  µCi/cc)

## ENVIRONMENTAL CHARACTERISTICS

- Normal temperature: +5 °C to +40 °C (+41 °F to +104 °F)
- Temperature limit: -5 °C to +55 °C (+23 °F to +131 °F)
- MTBF: > 20 000 hours, with preventive maintenance
- TID: 100 Gy ( $10^{+4}$  rad)

## PNEUMATIC CHARACTERISTICS

- Standard flow rate: 35 l/min (1.24 scfm)
- Pressure drop: 100 to 350 mbar (1.45 to 5.07 psi)

## MECHANICAL CHARACTERISTICS

- Dimensions: 1270 mm x 360 mm x 303 mm  
(50 in x 14.2 in x 12 in)
- Weight: ~ 26 kg (~ 57 lb)
- Color: gray RAL 7030 (decontaminable paint)

## ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: one RS232 and two isolated RS485
- Alarm relays: three SPDT relays
- I/O: two isolated analog outputs (0/4-20 mA)

## SIGNALING

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: three lights (red, yellow, green)

## REFERENCE STANDARDS

- Nuclear: IEC 60761
- EMC: 2014/30/EU and 2014/35/EU, IEC 61000-6-2 and IEC 61000-6-4

## VERSIONS

- 230 Vac or 120 Vac
- Hose length: 1.5 m (5 ft), 3 m (10 ft), 10 m (33 ft) or 20 m (66 ft)

## ACCESSORIES

- Calibration tools
- Software: MASS2™, RAMVISION™, SIMS2™ applications...
- USB converters
- Radiomodem (either customer specified or WRM2™)



**MIRION**  
TECHNOLOGIES

Copyright © 2024 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.