



DBR-2

DIS Dosimeter Reader



Nuclear
Power



Homeland
Security
& Defense



Industrial and
Manufacturing



Healthcare



Labs and
Education

OVERVIEW

The DBR-2 Dosimeter Reader is designed to read DIS-1, DIS-1H3 and EDIS-1 dosimeters. The dosimeter is simply inserted into the reader head slot for dose read-outs. The design of the slot prevents the dosimeter from being inserted incorrectly.

Just plug the DIS-1, DIS-1H3 or EDIS-1 dosimeter into the Dosimeter Reader and in a couple of seconds the Hp(10), Hp(0.07), Hp(3) or H*(10) doses are shown on the display and stored in a local buffer memory. The instant reading capability allows the user to control his/her dose on a daily basis and makes the monthly or quarterly change of the dosimeter unnecessary.

The control period can be indefinite (in excess of a year), because the dose readings can be transmitted via electronic method rather than physically sending the dosimeter away for reading and recording of official doses.

www.mirion.com

KEY FEATURES

- Stand-alone use or interface to WinELD Dose Management Software
- Display of Session and Assignment doses and Session dose reset capability
- EIA RS-232C serial or optional external 10Base-T Ethernet LAN interface
- Back-up batteries and internal buffer memory for off-line dose collection
- Portable table top design
- PTB approved configuration available

Health Physics

FUNCTIONAL CHARACTERISTICS

- Display of Hp(10), Hp(0.07), Hp(3) and H*(10) doses
- Reset of the Session Dose
- Display of Session/Assignment Doses
- Display of Remaining Dose Capacities
- Real time clock
- Easy-to-check calibration with optional DBR Reader Calibration Plug
- Display and keypad controlled by the WinELD software
- Assignment/Session reset controlled by the WinELD software
- Internal buffer memory for 256 off-line dose records

MECHANICAL CHARACTERISTICS

- 2x16 character alphanumeric LCD display with LED backlight, 9.5 mm (0.37 in) digits
- Heavy duty 16-key keypad
- Power on/off by key switch
- EIA RS-232C serial port or optional external 10Base-T Ethernet LAN adapter
- Table top mounting
- Gold plated connector for dosimeter reading
- Rugged metal case
- Size (WxHxD): 250 x 80 x 280 mm (9.84 x 3.15 x 11.02 in)
- Weight: 3.1 kg (6.8 lbs)

CONFIGURABLE OPERATIONS

- Session Dose reset in off-line mode
- Assignment or Session dose primary display
- Automatic dose print-out
- Sv/rem dose unit selection
- Keypad operation (enabled/disabled)
- «On-line», «Off-line» and «Please wait» texts can be customized by the WinELD software
- US or European Date/Time format

ENVIRONMENTAL CHARACTERISTICS

- Operating temperature: from +10°C to +40°C (50°F to 104°F)
- Storage temperature: from -10°C to +60°C (14°F to 140°F)
- Humidity: 90% RH (non condensing)

ELECTRICAL CHARACTERISTICS

- 15 VDC, 550 mA universal input voltage plug in power supply
- Built-in back-up battery, 1.2 Ah, for minimum 8 h operation
- Complies with CE standards

> CHINA - SHANGHAI

T: +86 21 6180 6920 | E: info-cn@mirion.com

> FINLAND - TURKU

T: +358 2 4684 600 | E: info-fi@mirion.com

> FRANCE - LAMANON

T: +33 (0) 90 595959 | E: info-fr@mirion.com

> GERMANY - HAMBURG

T: +49 40 85193 0 | E: info-de@mirion.com

> USA - SMYRNA, GEORGIA

T: +1 770 432 2744 | E: info-us@mirion.com

Copyright (c) 2014 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.