



RAMSYS™

PM 205S™

Beta Particulate Monitor



Continuously measuring the volumetric activity of a radioactive gaseous sample containing particulates.

DESCRIPTION

The PM 205S monitor forms part of the RAMSYS product line. It has been developed to continuously measure the volumetric activity of a radioactive gaseous sample containing particulates. The sample is drawn from discharge stacks, reactor building, ventilation ducts or working areas via a pumping system. It is then admitted into a detection unit where the particulates are trapped on a filter. It is typically used for monitoring particulate volumetric activity under normal operating and mild environment conditions.

This monitor can operate as a stand alone device or in conjunction with an iodine monitor (IM 201), and/or noble gas monitors (NGM 203, NGM 204, NGM 214, NGM 216) to form a complete monitoring system.

FEATURES

- ✓ 1E qualification and embedded safety related software
- ✓ Available under 10 CFR 50 App. B, ASME NQA-1 and IEC 61226 programs for safety related application

PM 205S™ BETA PARTICULATE MONITOR

PHYSICAL CHARACTERISTICS

- Radiation detected: beta
- Detector: 2" thin plastic scintillator + PMT + embedded LED (SB 70)
- Filter type: fiberglass 57 mm (2.24 in)
- Lead shield: 7.5 cm/4 π (3 in/4 π)
- Typical energy range: > 30 keV
- Typical measurement range: 3.7 10⁻² to 3.7 10⁺³ Bq/m³ (10⁻¹² to 10⁻⁷ μCi/cc)

ENVIRONMENTAL CHARACTERISTICS

- Normal temperature: +5 °C to +40 °C (+41 °F to +104 °F)
- Temperature limit:
 - Processing unit: -5 °C to +55 °C (+23 °F to +131 °F)
 - Detector: +0 °C to +60 °C (+32 °F to +140 °F)
- MTBF:
 - Processing unit: > 50 000 hours
 - Detector: > 40 years
- TID: 100 Gy (10⁺⁴ rad)
- Protection index: IP65 and IK07

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 28.3 l/min (1 scfm)
- Pressure drop: 50 mbar (0.73 psi)

MECHANICAL CHARACTERISTICS

- Dimensions: 889 mm x 1397 mm x 1651 mm (35 in x 55 in x 65 in)
- Weight: 700 kg (1543 lb)
- Color: gray RAL 7030 (decontaminable paint)
- Inlet tube connection: Ø 1 in
- Outlet tube connection: Ø 1/2 in

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: one RS232 (LPDU only) and two isolated RS485
- Alarm relays: three SPDT relays
- I/O: two isolated analog outputs and one isolated analog input (0/4-20 mA)

SIGNALING (Applicable to LPDU only)

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: three lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC 60761-1 and IEC 60761-2
- Environmental: IEC/IEEE 60780-323
- Seismic: IEC 60980, IEEE 344
- EMC: 2014/30/EU and 2014/35/EU, EPRI 102323, RG 1.180, IEC 61000-6-2 and IEC 61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- Local processing and display unit (LPDU) or local processing unit (LPU)
- With or without check source
- With or without heater
- PIS sampler

ACCESSORIES

- Calibration tools
- Software: MASS2™, RAMVISION™, SIMS2™ applications...
- USB converters
- Seismic qualified wall mounting bracket for LP(D)U
- Ethernet (LPDU version only)



MIRION
TECHNOLOGIES

Copyright © 2024 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.