



## RADIATION TOLERANT CAMERA

# R981™

*System Camera*



### FEATURES

- Class leading radiation tolerance
- Pan, tilt, zoom, video and power over three twisted pairs
- High resolution monochrome picture
- Radiation tolerant telemetry
- One 19 in. sub-rack to control up to eight cameras
- Eight channel lighting and microphone sub-racks
- RS-485 control of sub-racks
- Change cameras without adjustment
- Software protocol and hardware can address up to 128 channels of cameras and lighting
- Seismic qualification available
- Captions at the source
- Modular design for easy assembly/install
- Simple cable
- Integral version available
- Option available without pan and tilt

### APPLICATIONS

- Process monitoring
- Safeguard surveillance
- In-containment viewing
- Waste management
- Guidance and posting

### DESCRIPTION

Mirion Technologies is one of the world's most experienced suppliers of large turnkey television surveillance systems to the nuclear industry. Major multi-camera radiation tolerant system installations are an essential part of the process monitoring requirements for nuclear power stations and waste handling facilities. New safety requirements relating to plant life extensions and new power plant construction demand the use of television systems to continuously monitor machinery and key plant areas within secondary containment.

The R981 camera range has been specifically designed to suit these large multi-camera configurations. Alternatively, single camera channels can be supplied as ideal inspection and surveillance tools.

SPECIFICATIONS AND PERFORMANCE

CAMERA OUTSTATION			
<b>Housing Material</b>	Stainless steel	<b>Operating Dose Rate</b>	1 kGy/hour (Chalnicon tube)
<b>Operating Temperature Ambient</b>	0 to 55 °C (35 to 131 °F) (Chalnicon tube)	<b>Radiation Tolerance</b>	1 MGy [ <sup>60</sup> Co] (H <sub>2</sub> O); 10 <sup>8</sup> Rad [ <sup>60</sup> Co] (H <sub>2</sub> O)
<b>Camera Midpoint Connector</b>	24-way	<b>Weight</b>	Approximately 13 kg (28.7 lb)
<b>Maximum Operating Depth</b>	20 m (66 ft)	<b>Cable Connection</b>	18-way remote handling LEMO or 12-way Fischer
<b>Maximum Submersion Depth</b>	60 m (197 ft)	<b>Pan and Tilt</b>	Speed: 6° per second Travel: ±180° (adjustable)
<b>Size with Pan and Tilt</b>	294 x 267 x varying 241 to 320 mm (H x W x varying D) (11.6 x 10.5 x varying 9.5 to 12.6 in.)	<b>Sealing</b>	IP68 (IEC529) 60 m water depth (W.W. Fischer stainless steel connector type SE105Z069-27) IP66 (IEC529) fully washable (LEMO stainless steel remote handling cable connector type FZJ3N318TLMY)

CAMERA CHANNEL PERFORMANCE (CAMERA AND CCU COMBINED)	
<b>Horizontal Resolution</b>	550 HTV lines
<b>Sensitivity (faceplate)</b>	1 lux (Chalnicon tube)
<b>AGC Range</b>	-6 dB to 20 dB
<b>Signal to Noise Ratio</b>	43 dB (CCIR weighted, AGC at 0 dB)
<b>Geometric Distortion</b>	2% maximum

EIGHT CHANNEL CAMERA SYSTEM SUB-RACK	
<b>Nominal Power Supply Input</b>	100-120/200-240 V (auto-ranging); 50/60 Hz
<b>Operation Range</b>	85-132/170-264 V (auto-ranging); 47-440 Hz
<b>Power Requirement</b>	150 VA for a fully populated 8-channel CCU
<b>Outstation Cable Length</b>	300 m (984 ft) maximum CCU to camera (consult Mirion)
<b>Operating Ambient Temperatures</b>	Fully populated, convection cooling: 0 to 40 °C (32 to 104 °F) Up to 6 channels, convection cooling: 0 to 50 °C (32 to 122 °F) Fully populated, forced air cooling at 500 litres (132 gallons)/minute: 0 to 50 °C (32 to 122 °F)
<b>Relative Humidity</b>	80% for temperatures up to 31 °C decreasing linearly to 50% at 40 °C
<b>Size</b>	134 x 483 x 300 mm (H x W x D) (5.3 x 19 x 11.8 in.) (excluding handles and connectors)
<b>Weight</b>	7 kg (15.4 lb)

R981 NON-BROWING LENS OPTION	
<b>Lens</b>	Viewing Angle: In Air
<b>6:1 12 mm-72 mm zoom</b>	40° wide; 7° narrow
<b>6:1 24 mm-144 mm zoom</b>	21° wide; 3.5° narrow
<b>3:1 8 mm-24 mm zoom</b>	58° wide; 21° narrow

CCU CONNECTOR TYPES	
<b>AC Power</b>	IEC 320 plug (fitted with T4A fuse)
<b>Camera Inputs (8 off)</b>	15-way D type socket
<b>Video Outputs (8 off)</b>	75R BNC
<b>Genlock Input</b>	75R BNC (with 75R termination switch)
<b>Sync Pulse Output</b>	75R BNC
<b>Serial Control Input</b>	9-way D type plug
<b>Serial Control Loop Through</b>	9-way D type socket

OPTIONAL ACCESSORIES	
<b>Camera Attachments</b>	Camera allows for up to four attachment positions for a combination of microphone and lights
<b>In-air or Underwater Lights</b>	Up to 300 W using 50, 75 or 100 W lamps
<b>Lighting Sub-rack</b>	Eight Channel
<b>Microphone</b>	For in-air use only
<b>Microphone Sub-rack</b>	Eight Channel

SPC-143-EN-A\_DMD-08/2021

Copyright © 2021 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.

Specifications may vary according to system configuration. We reserve the right to modify or amend the information herein without prior warning. Please contact your Mirion representative for further information.

Mirion Technologies (IST) Ltd and Mirion Technologies (Imaging), LLC are ISO 9001:2015 certified companies (certificates available on request or at [www.mirion.com](http://www.mirion.com)).

Please note that the products and accessories described in this data sheet may be subject to UK export control or US re-export control. Please check with your authorized representative when enquiring about this product.

