



Osprey[®]

Universal Digital MCA Tube Base for Scintillation Spectrometry

The Osprey unit is a high-performance, fully-integrated multi-channel analyzer (MCA) tube base that contains everything needed to support scintillation spectrometry.

Designed for laboratory and field use, this compact unit has a high-voltage power supply (HVPS), preamplifier and a full-featured digital MCA. The Osprey digital MCA can be controlled through USB or Ethernet with no need to purchase two separate units – an industry first. One cable connects the Osprey digital MCA to the control and data acquisition system.

For desktop applications, power, and all communications are handled by a USB 2.0 port. In situations where networking and/or remote access are desired, the Ethernet 10/100BaseTX port can be used which provides power and communications via Power-over-Ethernet (PoE). An example of using the Osprey unit's networking capabilities is setting up a radiation monitoring system with multiple unattended detectors in remote locations. Ethernet can also be used in desktop applications instead of USB if needed. Coupled with the powerful Genie™ Spectroscopy Software Suite, the Osprey digital MCA takes scintillation spectrometry to a new level. Just connect probe and Osprey unit, connect the Osprey digital MCA to an available USB or Ethernet port, start the Genie software, and you are ready to acquire the spectrum.

The Genie Spectroscopy Software Suite is a comprehensive environment for MCA control, data acquisition, display, and analysis. It provides



FEATURES

- ✓ All-in-one HVPS, preamplifier, and digital MCA
- ✓ Compatible with standard 14-pin scintillation detectors using 10-stage PMTs, including NaI(Tl) and LaBr₃(Ce)
- ✓ Optional temperature-stabilized* NaI(Tl) and CeBr₃ probes
- ✓ USB 2.0 connection for PC plug-and-play
- ✓ Ethernet 10/100BaseTX (PoE) connection for network applications
- ✓ PHA, MCS, SCA, MSS, List, and Time-stamped List modes
- ✓ Fully supported by Genie Spectroscopy Software applications
- ✓ Optional software development kit with examples
- ✓ Diagnostic web GUI
- ✓ Compatible with Model 727 shield

independent support for multiple detectors, extensive networking capabilities, advanced data analysis, and comprehensive batch procedure capabilities. An OS independent software development kit (SDK) with examples is available and can be used without Genie software. The SDK is similar to the comprehensive set of programming tools available with the Mirion Lynx[®] II MCA. It allows expert users to develop platform independent applications for instrument control and data acquisition.

In addition, a diagnostic web graphical user interface (GUI) application is supplied with the Osprey unit, providing MCA and probe status information, network setup, and firmware upgrade functionalities.

The Osprey digital MCA features support for all commonly used spectrometry modes – PHA, MCS, SCA, MSS, List, and Time-stamped List – unmatched by any other tube-base MCA on the market. The Osprey unit provides a level of performance superior to many available desktop MCAs.

The Osprey digital MCA will accommodate standard 14-pin scintillation detectors using 10-stage PMTs. It also supports a suite of temperature-stabilized detectors designed specifically for the Osprey unit. The Mirion temperature-stabilized detectors use a patented* LED stabilization technique and feature a robust locking mechanism for increased reliability. In most detector configurations, the Osprey digital MCA is compatible with Model 727 laboratory lead shield.

Specifications


PROGRAMMABLE CONTROLS

- Gain
 - Coarse Gain: x1, x2, x4, x8 software programmable
 - Fine Gain: x1 – x5 software programmable
 - Total Gain: Product of Fine Gain and Coarse Gain, x1 – x40
- ADC: ADC 14-Bit 20 MHz Sampling
- ULD/LLD
 - ULD: 0% to 100% of Full Scale software programmable
 - LLD: 0% to 100% of Full Scale software programmable
- Detector Voltage: HVPS
 - 0 to +1300 V dc: 100 V/s ramping on power up and down
- Shaping
 - DSP Based Trapezoidal shaping filter operating at 80 MHz
 - Rise Time: 0.2 μ s – 5 μ s in 200 ns steps. Default: 1 μ s for NaI probe
 - Flat Top: 0 to 3 μ s in 100 ns steps. Default: 1 μ s for NaI probe

- Digital Spectrum Stabilization
 - Support for a stabilization source for non-stabilized probes
 - Support of temperature-stabilized probes
- BASE LINE RESTORER: Automatic with provision for adjustable BLR
- FAST DISCRIMINATOR THRESHOLD: Automatic with provision for adjustable FDisc
- PUR GUARD: Programmable guard time 1.1 to 2.5 times shaping

INPUTS/OUTPUTS

- Standard 14-pin PMT socket and Mirion proprietary 8-pin socket
- USB 2.0
- Ethernet 10/100BaseTX
- GPIO: Three freely assignable MCX connectors
 - TTL compatible, minimum pulse width for inputs >50 ns, all inputs have software selectable polarity
 - Coincidence/Anti-coincidence
 - PHA External Start/Stop: Start/Stop Mode (Start Only, Stop Only, and Start and Stop) or Suspend and Resume Mode (can also be an output to control other devices)
 - MCS External Start/Stop: Start/Stop Mode (Start Only, Stop Only, and Start and Stop) or Suspend and Resume Mode (can also be an output to control other devices)
 - External Time Sync (can also be an input or an output to control other devices) for the following modes:
 - List (Sync. rate from external source or master to sync. time stamps of events)
 - MSS (Sync. from external source or master to advance to next spectral group)
 - Aux Counters and SCA Counters (Sync. can be used to control the start of interval timer and synchronize the interval timer at each sync event)
 - Aux Counter In: Auxiliary Counter Input
 - MCS Input: External MCS input, TTL pulse
 - MCS Channel Advance: External MCS Channel Advance; TTL pulse
 - MCS Sweep Advance: External MCS Sweep Advance input; TTL pulse
 - SCA Outputs: Up to three; each of these outputs can be selected from one of the six internal SCAs
 - ICR Out: Incoming count rate output
 - Acquisition Out: Acquisition status.
 - General Purpose Input/Output: Output signal to drive external devices or input signal to monitor external device's status



*US Patents 7,005,646 B1 and 7,049,598 B1

ACQUISITION MODES

- PHA
 - PHA Channels: 256 to 2048 Channels, supports two memory groups of up to 2048 channels each
 - Preset: ROI Counts (Integral), Real or Live Time timers
 - Real and Live Time Resolution: 0.01 s
 - Preset Time: 0 to $>4 \times 10^7$ s
 - Control: Internal or External Start/Stop control
 - LTC accuracy: 5% (3% typical) up to 50 kcps
 - LTC method: proprietary
- MCS
 - Dwell range: 1 μ s to 999 seconds in 1 μ s steps
 - Sweep range: 1 to $2^{32} - 1$
 - Preset Sweep Counter: 0 to $2^{32} - 1$ Sweeps (0 implies "Forever")
 - MCS input selection: PHA ROI, external TTL or Fast Discriminator
 - Dwell selection: internal or external
 - MCS Channels: 256 to 2048 Channels, supports two memory groups of up to 2048 channels each

The following advanced modes of operation are accessible through the optional SDK.

- SCA
 - Channels 6
 - Preset Modes Live Time, Real Time
 - SCA Modes Automatic, Manual, AutomaticEx, External Sync
 - Size of Counter for each SCA Channel 32-bits
 - LLD and ULD for each SCA Channel 0% to 100% Full Scale Software Programmable
 - SCA Signal Output for selected channel 200 ns output pulse for each event can be mapped to a GPIO connector
- MSS
 - Data acquired into two memory groups, alternating between the two in a "ping-pong" fashion when a preset time parameter is reached
 - Ability to use External Sync. to switch between groups
- List/Time-Stamped List
 - Latency: 100 ms (Only when streaming mode is supported)
 - External time base support (Use of External Sync.)
 - Time-stamp resolution selection of 1 μ s or 100 ns
 - Maximum event rate 100 000 pulses/sec
- AUX Counter
 - TTL compatible, minimum pulse width for input >50 ns
 - AUX Counter Modes Automatic, Manual, AutomaticEx, External Sync

PERFORMANCE

- Channel Configurations
 - Total channels 8192
 - Configurable as two groups of 2048, 1024, 512 or 256 channels for PHA and MCS (can be simultaneous)
 - Bits per channel 32
- Integral Non-linearity: $\pm 0.025\%$ of full scale over the top 99% of the selected range
- Differential Non-linearity: $\pm 1\%$ over the top 99% of the range including the effects from integral non-linearity
- Gain Drift: <75 ppm/ $^{\circ}$ C after 15 minutes of operation
- Incoming Count Rate (ICR): >250 K cps ICR if not limited by probe/detector

HIGH VOLTAGE POWER SUPPLY

- Output is current limited and short-circuit protected
- HVPS
 - OUTPUT: 0-1300 V at 50 μ A max
 - RIPPLE: 1 mV – ACCURACY: 3% Full Scale
 - SETTING RESOLUTION: 14-bit (1/16 384)

INDICATORS

- BUSY
- Status: HV/Stabilized Probe.
- ICR

DETECTORS

- 14-pin scintillation detector
- Mirion temperature-stabilized probes

SOFTWARE & USER INTERFACE

- Genie-Single or Genie-Multi Spectroscopy Software Suite for quantitative analysis applications (1-year, 3-year, or perpetual licenses available)
- GenieLite-Single or GenieLite-Multi Spectroscopy Software for acquisition only (1-year, 3-year, or perpetual licenses available)
- SDK: Optional software development kit that is OS independent, Genie software not required
- Diagnostic Web GUI: OS and browser independent, Genie software not required

COMPUTER REQUIREMENTS

The minimum computer requirements are those specified for the current version of the Genie software. See the Genie Spectroscopy Software data sheet for more details.

POWER

- Main power will be supplied by either the USB port or IEEE 802.3af-compliant Power over Ethernet (PoE)
- Power consumption USB: < 2 Watt
- Power consumption PoE: < 3 Watt

PHYSICAL


- Size: 62 mm (2.44 in.) diameter – 108 mm (4.25 in.) length
- Weight: 280 g (9.9 oz)

ENVIRONMENTAL

- TEMPERATURE: -10 to +50 °C (+14 to +122 °F)
- HUMIDITY: 85% non-condensing
- Meets the environmental conditions specified by EN 61010, Installation Category I, Pollution Degree 2

PHYSICAL

- EMC (Emissions and Immunity):
 - EN61326:2006
 - EN61000-3-2:2008
 - EN61000-3-3: 2008
 - EN61000-4-2: 2008
 - EN61000-4-3: 2008
 - EN61000-4-4: 2004
 - EN61000-4-5: 2005
 - EN61000-4-6: 2008
 - EN61000-4-11: 2004
 - EN61000-4-8:2001
- NRTL LISTED (Safety):
 - CAN/CSA C22.2 No. 61010-1-04
 - UL61010-1:2004
 - IEC61010-1:2001 2nd edition
 - EN61010-1:2001 2nd edition



Ordering Information

- OSPREY-DTB: Digital tube-base MCA with 3 m (10 ft) USB cable, 3 m (10 ft) crossover Ethernet cable, 3 m (10 ft) Ethernet cable, PoE input injector (110/220), 1.2 m (4 ft) MCX-BNC cables, 3 pcs
- LABR-1.5x1.5 Detector: 14-pin 1.5 x 1.5 in. non-stabilized LaBr₃ probe
- NAIS-2x2 Detector: 8-pin 2 x 2 in. LED temperature-stabilized NaI probe
- NAIS-3x3™ Detector: 8-pin 3x3in. LED temperature-stabilized NaI probe
- CEBRS-1.5x1.5™ Detector: 8-pin 1.5x1.5in. LED temperature-stabilized CeBr₃ probe
- CEBRS-2x2™ Detector: 8-pin 2x2in. LED temperature-stabilized CeBr₃ probe
- Model 802 Detector: 14-pin 2 x 2 in. or 3 x 3 in. non-stabilized NaI probe
- OSPREY-SDK: OS independent Software Development Kit
- OSPREY-E03L: 3 m (10 ft) Ethernet cable with a right angle plug for use with Model 727 laboratory lead shield



Copyright © 2024 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.